

# Network Camera Firmware Version: V5.5.4 Release Note(External) (2018-02-06)

	Firmware Version:	V5.5.4
	SDK Version:	V5.2.7.45 build170612
	Play Library (PlayCtrl.dll)	V7.3.3.61 build170510
Firmware	Encapsulation Library (SystemTransform.dll)	V2.5.2.5
Basic Information	Voice intercom library (AudioIntercom.dll)	V1.4.0.3
	iVMS-4200	V2.5.13.2 build170709
	IE Client version	V4.0.1 build171218
		V3.0.6.33

## **Hikvision Firmware V5.5.4 Features**

### \*for DS-2CD1X23, HiLook, DS-2CD2X21G0 Cameras

#### 1. New Features

- White light switch control strategy is optimized.
- 1) Support sensitivity and different levels of light switch ambient brightness.
- 2) Optimize day and night switch algorithm to solve the issue of white light oscillation.
- 3) <u>Support HLC and SmartIR function which can solve explosion issue in some highlight scenes.</u>
- <u>SN (Serial Number) is the combination of numbers and letters.</u>
- English SN (Serial Number) is supported in watermark.
- 2. Improved Features
  - The video stream is default for the camera only support linein.
  - Solve the issue that motion detection will always be triggered when enabling IR.



## • <u>The sub stream resolutions are changed to 640\*480(VGA), 640\*360, 320\*240(QVGA). Default</u> resolution of sub stream is 640\*360.

#### **Compatibility Update**

- <u>HIKCGI version: V2.0;</u>
- ISAPI version: V2.4;
- ONVIF version: V1612, official test tool version: V1701;
- <u>Milestone:</u>
  - 1. Milestone Enterprise 8.1a(10.2a), Milestone drive version (Driver 9.1), test HIKCGI
  - 2. Milestone software version (Milestone Corporate 11.1a), Milestone drive version (Driver 9.1), test HIKCGI

#### • <u>Avigilon:</u>

- 1. Control Center: V5.10.12.2;
- 2. Test ONVIF.

#### • Excaqvision:

- 1. Version: 8.4.2
- 2. Protocol: HIKCGI, ONVIF

### • NAS(Only test for Brainaire):

DS-A2016R, DS-A1016RS V2.2.0-7

#### • <u>Tested NVRs:</u>

DS-96256NI-I24/H(baseline V3.2.8\_170213\_05)

96000 I Series

96000NI-I Series NVR (V3.6.21)

E Series: DS-7732NI -E4/16P(V3.4.92)

G Series: DS-7608NI-G2/4P(V3.4.1 build 151225)

K Series: V3.4.93

Netra DVR: DS-9016HFI-ST(V3.4.3)

Note: The compatibility of IPC and NVR models in the same NVR series is the same.

#### Tested Keyboard:

DS-1600KI V2.0.0

DS-1006KI V1.0



## **Customer Impact and Recommended Action**

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

#### <u>Remarks:</u>

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd. No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China Tel: +86-571-8807-5998 FAX: +86-571-8993-5635 Email: overseabusiness@hikvision.com

Supported Product List (1X23/HiLook/2X21G0)			
roduct Category	Model Number	Product Description	
Fixed Bullet	DS-2CD1023G0-I	2MP, IR, DWDR	
Fixed Dome	DS-2CD1123G0-I	2MP, IR, DWDR	
Fixed Turret	DS-2CD1323G0-I	2MP, IR, DWDR	
EXIR VF Bullet	DS-2CD1623G0-I	2MP, IR, DWDR	
EXIR VF Dome	DS-2CD1723G0-I	2MP, IR, DWDR	
Fixed Bullet	IPC-B120H	2MP, IR, DWDR	
Fixed Dome	IPC-D120H	2MP, IR, DWDR	
Fixed Turret	IPC-T120H	2MP, IR, DWDR	
EXIR VF Bullet	IPC-B620H-V/Z	2MP, IR, DWDR	



EXIR VF Dome	IPC-D620H-V/Z	2MP, IR, DWDR
Fixed Bullet	DS-2CD2T21G0-I	2MP, IR
Fixed Bullet	DS-2CD2T21G0-IS	2MP, IR
Fixed Bullet	DS-2CD2321G0-I/NF	2MP, IR
Fixed Dome	DS-2CD2121G0-I	2MP, IR
Fixed Dome	DS-2CD2121G0-IS	2MP, IR
Fixed Dome	DS-2CD2121G0-IW	2MP, IR, WIFI
Fixed Dome	DS-2CD2121G0-IWS	2MP, IR, WIFI