

Network Camera Firmware Version: V5.5.70 Release Note (External) (2018-10-17)

	Firmware Version:	V5.5.70 build180929	
	SDK Version:	V5.2.7.45 build170612	
	Play Library (PlayCtrl.dll)	V7.3.5.0	
Firmware	Encapsulation Library	V2.5.2.15	
	(SystemTransform.dll)		
Basic Information	Voice intercom library	V1.4.0.6	
	(AudioIntercom.dll)		
	iVMS-4200	V2.5.13.2 build170709	
	IE Client version	V4.0.1 build170711	
		V3.0.6.26	

Hikvision Firmware V5.5.70 build 180929 Features

*for (1021G0-IDW1) Cameras

- 1. New Features
 - Newly support H.264 2MP consumer Wi-Fi camera DS-2CV1021G0-IDW1
 - DS-2CV1021G0-IDW1 supports SD card, reset button, red & blue double flash indicator light
 - <u>DS-2CV1021G0-IDW1 supports H.264+, sub stream support MJPEG, default setting of</u> main stream is H.264+, does not support smart event
 - <u>DS-2CV1021G0-IDW1 supports adaptive activation mode when connect with NVR or</u> <u>Hik-Connect APP, supports Smart Config</u>
 - For reset bouton, support push reset button for 10 seconds when camera is started to reset camera, camera will reboot automatically after reset complete.
 - <u>Consumer Wi-Fi camera supports adaptive activation mode</u>



- Consumer Wi-Fi Camera is inactive status by default
- Using Hik-Connect APP scan QR code to configure Wi-Fi camera, inactive camera will be activated and password is the combination of admin and verification code
- Using Smart Link on Wi-Fi NVR to connect camera, camera needs to be manually activated
- NVR models that support Smart Link:
- HiWatch series models, HWN-2104MH-W, HWN-2108MH-W
- Hikvision baseline models, DS-7104NI-K1/W/M, DS-7108NI-K1/W/M
- Firmware version of NVR that support Smart Link, V3.4.98

2. Improved Features

- There are some default settings of Wi-Fi camera, DHCP is enable, Video Type is video stream, Bitrate Type is variable, Audio Encoding is G.711ulaw and Environmental Noise Filter is ON
- Motion Detection of Wi-Fi camera is enable, Linkage Method configure channel record and picture upload by default, Percentage of Record and Percentage of Picture change to 95 and 5
 When H.264+ of Wi-Fi camera in kit setting to ON, Stream Adaption cannot be set, and when Stream Adaption setting to enable, H.264+ cannot be set

Compatibility Update

- HIKCGI version: V2.0;
- ISAPI version: V2.4;
- ONVIF version: V1612, official test tool version: V1701;
- <u>Milestone:</u>
 - 1. Milestone Enterprise 8.1a(10.2a), Milestone drive version (Driver 9.1), test HIKCGI
 - 2. Milestone software version (Milestone Corporate 11.1a), Milestone drive version (Driver 9.1), test HIKCGI
- <u>Avigilon:</u>
 - 1. Control Center: V5.10.12.2;
 - 2. Test ONVIF.
- Excaqvision:
 - 1. Version: 8.4.2



2. Protocol: HIKCGI, ONVIF

• NAS(Only test for Brainaire):

DS-A2016R, DS-A1016RS V2.2.0-7

<u>Tested NVRs:</u>

DS-96256NI-I24/H(baseline V3.2.8_170213_05)

96000 I Series

96000NI-I Series NVR (V3.6.21)

E Series: DS-7732NI -E4/16P(V3.4.92)

G Series: DS-7608NI-G2/4P(V3.4.1 build 151225)

K Series: V3.4.93

Netra DVR: DS-9016HFI-ST(V3.4.3)

Note: The compatibility of IPC and NVR models in the same NVR series is the same.

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

<u>Remarks:</u>

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd. No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China Tel: +86-571-8807-5998 FAX: +86-571-8993-5635 Email: overseabusiness@hikvision.com



Supported Product List	(DS-2CD1X21G0-IDW1)
------------------------	---------------------

Product Category	Model Number	Product Description
Wi-Fi fixed bullet	DS-2CV1021G0-IDW1/NF(T)	Built-in Wi-Fi, 2MP,Kit
Wi-Fi fixed bullet	DS-2CV1021G0-IDW1	Built-in Wi-Fi, 2MP